


EZ-Bend™ 4.8 Cable



A Furukawa Company

The **EZ-Bend™ 4.8 Cable**, available in indoor/outdoor, riser, plenum, and low-smoke zero-halogen constructions, **can be routed around corners and stapled** using traditional fast and easy copper wire installation practices, with negligible signal loss. Ideal for aggressive routing environments where space is at a premium, the EZ-Bend 4.8 Cable offers **reliable support for MDU and in-home wiring applications**.



EZ-Bend 4.8 Optical Cable Cross-Section

Features:

- 4.8 diameter ruggedized simplex cordage
- Less than 0.1 dB macrobending attenuation at 1550 nm for 1 turn at 5 mm fiber bend radius
- Less than 0.3 dB macrobending attenuation at 1550 nm when subjected to MDU Simulation Test called out by Verizon TPR.9424 FOC Document
- Solid construction fiber with macrobending performance far better than ITU G.657B requirements
- Backward compatible with installed G.652D fibers
- Available in alternative colors upon request
- Conform to UL Riser and Plenum fire ratings
- Compliant with Telcordia 409 & ICEA S-85-596 requirements
- UV and fungus resistant jacketing
- Dry water-blocked core to protect against water ingress
- Reinforced solid jacket construction naturally limits cable bending to control macrobending attenuation and protect fiber reliability
- Featuring EZ-Bend Optical Technology, a breakthrough developed by OFS Labs

Benefits:

- **“Copper-like” installation process:** Can be routed around corners using familiar copper wire practices, and stapled
- **Faster, easier installation:** no extra steps to install bend limiters, conduits, or raceways
- **Compact installation and storage:** Conforms to building; slack fits in small storage spaces
- **Fast, easy, low loss splicing** to G.652D fiber with existing core and clad aligned splice equipment
- **Familiar, standard connector termination:** Solid fiber construction can be terminated using standard optical connectors and polishing techniques
- **Familiar connector endface cleaning** using same process as with existing G.652 solid construction fiber
- **MDU and in-home optimized:** Ideal for in-residence wiring and difficult installation routes in MDU overbuilds
- **Greener Solution:** Free of heavy metals and RoHS-compliant; solution uses less total materials and energy than copper solutions

Performance

| Flame Performance | Mechanical and Environmental Performance | Temperature Range |
|---|--|---|
| Riser: UL 1666 compliant | Telcordia GR-409, ICEA S-85-596 compliant | Installation: 32° F to 104° F (0° C to 40° C) |
| Plenum: NFPA 262 (UL 910) compliant | | Operation: -40° F to 158° F (-40° C to 70° C) |
| Non-Halogen: IEC 60332-3c and IEC 61034-2 compliant | | Storage: -40° F to 158° F (-40° C to 70° C) |
| Attenuation @ | 1310 nm | 1550 nm |
| Maximum Attenuation | 0.4 dB/km | 0.3 dB/km |
| Typical Attenuation | 0.35 dB/km | 0.25 dB/km |

Specifications

| Cable Type | Jacket Color * | Part Number | Maximum Tensile Rating N (lb) | Nominal Weight kg/km (lb/100 ft) | Standard REELEX Box Length † |
|------------------------|----------------|-----------------|-------------------------------|----------------------------------|------------------------------|
| Riser | White | LG4.8C-001A-DRW | 440 N (100 lb) | 21.5 kg/km (1.44 lb/100 ft) | 457.2 m (1500 ft) |
| Plenum | White | LG4.8C-001A-DPW | 440 N (100 lb) | 26.1 kg/km (1.75 lb/100 ft) | 457.2 m (1500 ft) |
| Low-Smoke Zero Halogen | White | LG4.8C-001A-DHW | 440 N (100 lb) | 23.3 kg/km (1.57 lb/100 ft) | 500 m (1640.4 ft) |
| Indoor/Outdoor Riser | Black | IO4.8C-001A-DRK | 440 N (100 lb) | 23.3 kg/km (1.57 lb/100 ft) | 457.2 m (1500 ft) |

* Other colors available upon customer request.

† Alternative lengths available on standard premise spools. Contact OFS for more details.

Example of Standard Sheath Marking [Custom sheath marking available upon request]

White-Jacketed Riser-Rated Ruggedized Drop Cable with EZ-Bend Technology:

OFS EZ BEND ULTRA BEND INSENSITIVE OPTICAL DROP CABLE -C- LG4.8C-001A-DRW C(UL) US TYPE OFNR [CSA OFN FT4] {lot number} ~nnnnn FEET



Use electronic files, available at:
www.ofsoptics.com - Use less paper

EZ-Bend is a trademark of OFS FITELE, LLC.

For additional information please contact your sales representative. You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) from inside the USA or 1-770-798-5555 from outside the USA.

OFS reserves the right to make changes to the prices and product(s) described in this document in the interest of improving internal design, operational function, and/or reliability. OFS does not assume any liability that may occur due to the use or application of the product(s) and/or circuit layout(s) described herein.

This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.

Copyright © 2009 OFS FITELE, LLC.
All rights reserved, printed in USA.

OFS
Marketing Communications
fap-251-0309



A Furukawa Company